

1280 Enterprise™ Series

Programmable Color Touchscreen Weight Indicator/Controller



Standard Features

- Seven-inch, 800 x 480 pixel, graphical color display that adjusts for ambient light conditions
- Twelve-inch, 1280 x 800 pixel, graphical color display that adjusts for ambient light conditions
- Highly customizable graphical user interface
- Three different enclosure types: universal with tilt stand, panel mount and wall mount
- Resistive color touchscreen that can be used with gloves
- On-screen keyboard available during entry mode or use an external keyboard
- Multi-language operation and text entry
- Keypad for scale operations, numeric entry and navigation
- More than 150 built-in functions for programming
- Customize applications and data tables with iRite™ software
- Built-in web server for remote access, systems integration and data monitoring
- Up to eight scales supporting five scale types:
 - Analog load cell scales
 - Total scales
 - Serial scales
 - Program scales
 - iQube2 scales
- Multi-range/interval weighing functions
- Eight digital I/O for control and pulse count
- 100 setpoints, 18 configurable setpoint types
- 22 soft keys with 10 user-defined
- Two RS-232 and RS-485 serial ports
- USB, Ethernet TCP/IP, Wi-Fi Direct and Bluetooth® ports

Options

- Six option slots that support:
 - A/D scale channels
 - Analog Input/Thermocouple
 - Digital input and outputs
 - Analog outputs
 - Serial ports
 - Four channel dry-contact relay
 - Various protocol interfaces

Additional models are available with the approvals shown below. Please consult the factory for part numbers.

Approvals*



* Touch-only units pending approvals

Specifications

Power:

AC voltages: 100-240 VAC; 50-60 Hz
DC voltages: 11-30 VDC
Consumption: 60 W

Excitation Voltage:

10 ± 0,5 VDC
16 x 350Ω or 16 x 700Ω load cells per A/D card

Analog Signal Input Range:

-60 mV to 60 mV

Analog Signal Sensitivity:

0,3 μV/graduation minimum at 7,5 Hz–120 Hz
1,0 μV/graduation recommended

A/D Sample Rate:

7,5 to 960 Hz, software selectable

Resolution:

Internal: 8 million counts/8.000.000
Display: Seven digits/1.000.000

System Linearity

± 0,01% full scale

Digital I/O:

Eight I/O channels on CPU board
Optional 24-channel I/O expansion boards

Communication Ports:

Port 1 & 2: Full duplex RS-232 with CTS/RTS, RS-422/485
Baud Rate: 1200 to 115200
Port 3: USB 2.0 Device (Micro)
Port 4: Bluetooth® SPP 2.1+EDR
USB Host: (2) Type A Connectors max 500 mA
Ethernet: Wired 10/100 Auto-MDX
Ethernet: Wireless 802.11 b/g/n 2.4GHz

Onboard:

Selectable filters: Three stage, Adaptive or Damping
Embedded Linux® OS
8 GB eMMC (system use)
1 GB DDR3 RAM
460 MB onboard database (SQLite) storage
Up to 32 GB micro SD card (sold separately)

Display:

178 mm, 800 x 480 pixel, graphical color TFT display 500 or 1000 NIT
305 mm, 1280 x 800 pixel, graphical color TFT display 1500 NIT

Keys/Buttons:

22-key membrane panel, tactile buttons, on-screen keyboard for text and numeric entry, USB port for flash drive, keyboard and printer

Temperature Range:

Certified: -10°C to 40°C
Operating: -20°C to 55°C

Weight:

Universal enclosure: 5 kg
Panel mount enclosure: 4 kg
Wall mount enclosure: 10 kg
Panel mount 178 mm touch-only enclosure: 3 kg
Panel mount 305 mm touch-only enclosure: 5 kg

Rating/Material:

Stainless steel 304 enclosure
Universal: IP69K
Wall mount: IP66
Panel mount: IP69K, NEMA Type 4X and 12

Warranty:

Two-year limited warranty

EMC Immunity:

EN 50082 Part 2 IEC EN 61000-4-2, 3, 4, 5, 6, 8, and 11

Approvals:

NTEP CC 15-00/Class III/IIIL 10,000d
Measurement Canada AM-5980C, Class III/IIIL HD 10,000d
OIML R76/2006-NL1-16.04 Class III/IIIL 10,000d
EU Test Certificate TC8596
UL/cUL Listed (universal)
UL/cUL Recognized (panel mount)
CE Marked



Measurement
Canada
Approved



1280 Enterprise™ Series

Programmable Color Touchscreen Weight Indicator/Controller



7-inch model with keypad



7-inch touch-only model




12-inch touch-only model


Numeric Keypad Models:



1280-2



1280-3




1280-4

Universal (1280-2) Dimensions			
A	276 mm	B	158 mm
C	235 mm	D	126 mm
E	229 mm	F	318 mm
G	133 mm		


Wall Mount (1280-3) Dimensions			
A	379 mm	B	279 mm
C	463 mm	D	479 mm
E	499 mm	F	361 mm
G	205 mm		

Panel Mount (1280-4) Dimensions			
A	229 mm	B	229 mm
C	15 mm	D	136 mm
E	8 mm		

Touch-only Models:



1280-5



1280-6

7-inch Touch-only (1280-5) Dimensions			
A	9.00 in (229 mm)	B	6.22 in (158 mm)
C	0.58 in (15 mm)	D	5.34 in (136 mm)
E	0.32 in (8 mm)		

12-inch Touch-only (1280-6) Dimensions			
A	14.00 in (356 mm)	B	10 in (254 mm)
C	0.58 in (15 mm)	D	5.34 in (136 mm)
E	0.32 in (8 mm)		

1280 Enterprise™ Series

Programmable Color Touchscreen Weight Indicator/Controller

Generate a 1280 Enterprise Series Model Reference Code

This reference number can be used at time of ordering.



ENCLOSURE TYPE	POWER TYPE	CORD TYPE	DISPLAY TYPE	OPTION CARDS ALL SLOTS MUST BE FILLED
1 Universal (1280-2) 2 Panel (1280-4) 3 Wall (1280-3) 4 Touch-only Panel 7 in (1280-5) 5 Touch-only Panel 12 in (1280-6)	1 AC 2 DC	1 NEMA 5-15 Universal - None 3 CEE 7/7 Universal 4 NEMA 5-15 Wall 5 CEE 7/7 Wall	1 500NIT 7 in Universal 2 1000NIT 7 in Universal 3 500NIT 7 in Panel/Wall 4 1000NIT 7 in Panel/Wall 5 1500NIT 12 in Panel	A Blank <i>If no option, controller will need 6 blanks</i> B Single A/D Scale C Dual A/D Scale D 24 Channel Digital I/O E Dual Serial Channel F 4-dry Contact Relay G Single Analog Out H Dual Analog Out I Analog Input J EtherNet/IP K DeviceNet L ProfiNet M Modbus TCP N Profibus DP O EtherCat P PowerLink

Part Number

Part #	Reference #	Description	Power	Display	Option Installed	Price
Universal Enclosure with 500 NIT Display (1280-2)						
171441 ††	1131BAAAAA	1280 Universal	100-240 VAC	500 NIT	Single Scale Card	Consult
172188 ††	1131CAAAAA	1280 Universal	100-240 VAC	500 NIT	Dual Scale Card	Consult
Panel Mount Enclosure with 500 NIT Display (1280-4)						
171663*	21-3BAAAAA	1280 Panel Mount	100-240 VAC	500 NIT	Single Scale Card	Consult
172186*	21-3CAAAAA	1280 Panel Mount	100-240 VAC	500 NIT	Dual Scale Card	Consult
Wall Mount Enclosure with 500 NIT Display (1280-3)						
174143 ††	3153BAAAAA	1280 Wall Mount	100-240 VAC	500 NIT	Single Scale Card	Consult
174145 ††	3153CAAAAA	1280 Wall Mount	100-240 VAC	500 NIT	Dual Scale Card	Consult
Wall Mount Enclosure with 1000 NIT Display (1280-3)						
172185 ††	3154BAAAAA	1280 Wall Mount	100-240 VAC	1000 NIT	Single Scale Card	Consult
172187 ††	3154CAAAAA	1280 Wall Mount	100-240 VAC	1000 NIT	Dual Scale Card	Consult
Touch-only 7 inch with 500 NIT Display (1280-5)						
186618 *	41-3BAAAAA	1280 Touch-only 7 in	100-240 VAC	500 NIT	Single Scale Card	Consult
Touch-only 12 inch with 1500 NIT Display (1280-6)						
186465 *	51-5BAAAAA	1280 Touch-only 12 in	100-240 VAC	1500 NIT	Single Scale Card	Consult

* Power cable not included



†† CEE 7/7 plug (Euro)

1280 Enterprise™ Series

Programmable Color Touchscreen Weight Indicator/Controller

INDICATORS / CONTROLLERS

www.ricelake.com/global | Phone: +31 (0) 26 472 1319

RICE LAKE

Single A/D Scale



Excitation Voltage:
10 VDC bi-polar, 4 or 6 wire sensing
16 x 350 ohms per channel
Analog Input Signal:
-10 to +40 mV

Part #	Description	Price
164085	Single scale A/D	Consult
166957	A/D sealing kit	Consult

Dual A/D Scale



Excitation Voltage:
10 VDC bi-polar, 4 or 6 wire sensing
8 x 350 ohms per channel
Analog Input Signal:
-10 to +40 mV

Part #	Description	Price
164683	Dual scale A/D	Consult
166957	A/D sealing kit	Consult

Digital I/O



24 channels, configurable as inputs or outputs. Inputs: 5 VDC max, active low; Outputs: 20 mA max per channel, active low; 5 VDC source available: 500 mA max

Part #	Description	Price
164684	Digital I/O	Consult
170008	DIO adapter, includes 60 pin flat ribbon cable, 24 in	Consult
170009	DIO adapter, includes 60 pin round cable, 60 in	Consult
170736	DIO adapter, includes 60 pin cable and cord grip, 60 in	Consult

For 24 I/O ribbon cable required.

Dual Serial Channel



Two-channel, full duplex RS-232 with CTS/RTS, RS-485 or RS-422, 1200-115200 baud

Part #	Description	Price
164685	Dual serial channel	Consult

Single Analog Out



16 bit, voltage output 0-10 VDC, current output 0-20mA, 4-20mA

Part #	Description	Price
165366	Single analog out	Consult

Dual Analog Out



16 bit, voltage output 0-10 VDC, current output 0-20mA, 4-20mA

Part #	Description	Price
164686	Dual analog out	Consult

Relay Card



Relay four-dry contact, max current 3A @ 30 VDC, 3A @250VAC

Part #	Description	Price
164689	Relay card	Consult

Analog Input



Analog Input Signal:
±10VDC, ±100mV, 0-20mA

Part #	Description	Price
164687	Dual analog input	Consult

Data Exchange with PLC/DCS Systems

EtherNet/IP



Part #	Description	Price
165792	EtherNet/IP	Consult

DeviceNet



Part #	Description	Price
165793	DeviceNet	Consult

Profinet



Part #	Description	Price
165794	Profinet	Consult

Modbus TCP



Part #	Description	Price
165796	Modbus TCP	Consult

Profibus DP



Part #	Description	Price
165795	Profibus DP	Consult

EtherCAT



Part #	Description	Price
179533	EtherCAT	Consult

PowerLink



Part #	Description	Price
182319	PowerLink	Consult

1280 Enterprise™ Series


Programmable Color Touchscreen Weight Indicator/Controller

Grayhill Relays and Racks



Part #	Description	Price
52332	Two-channel input relay, 2.5-28 VDC	Consult
52318	Two-channel input relay, 120 VAC	Consult
52319	Two-channel input relay, 240 VAC	Consult
52331	Two-channel input relay, 10-32 VDC	Consult
52316	Two-channel output relay, 120-140 VAC at 2 amp	Consult
52317	Two-channel output relay, 240-280 VAC at 7 amp	Consult
71376	Two-channel output relay, 3-60 VDC at 1 amp	Consult
71377	Two-channel output relay, 0-200 VDC/VAC at 1,5A/10W (dry contact)	Consult
84698	Two-channel output relay, inductive load, 120-140 VAC at 2A	Consult
84699	Two-channel output relay, inductive load, 240-280 VAC at 2A	Consult
52312	Eight-channel relay rack, panel mount and wall mount, requires 50-Pin flat or round ribbon cable - 4 slots	Consult
52314	16-channel relay rack, panel mount and wall mount, requires 50-Pin flat or round ribbon cable - 8 slots	Consult
52315	24-channel relay rack, panel mount and wall mount, requires 50-Pin flat or round ribbon cable - 12 slots	Consult
170008	Cable, 60-Pin flat ribbon with 50-Pin adapter, 610 mm length	Consult
170009	Cable, 60-Pin round with 50-Pin adapter, 1.524 mm length	Consult
170736	Cable, 60-Pin round with cord grip and 50-Pin adapter, 1.524 mm length	Consult

Options


Part #	Description	Price
Manuals and Software		
77925	Revolution scale software	Consult
166046	Manual, Operation	Consult
167659	Manual, Technical	Consult
167660	CD, 1280 Documents	Consult
164939	8 GB Micro SD card with SD and USB adapter	Consult
173046	USB flash drive, 1 GB	Consult




Unsealed Connectors



Sealed Connector



Sealed Receptacle



Options

Part #	Description	Price
Primary Component Parts		
163400	7 in 500 NIT display	Consult
163399	7 in 1000 NIT display	Consult
182992	12 in 1500 NIT display	Consult
179992	CPU board assembly includes face plate & fan plate	Consult
160758	Back Plane board	Consult
162693	AC power supply board	Consult
162694	DC power supply board	Consult
164121	Overlay, keypad, for panel & wall mount	Consult
164120	Overlay, touchscreen, for panel & wall mount	Consult
161731	Overlay, keypad, for universal	Consult
161730	Overlay, touchscreen, for universal	Consult
178498	Overlay, touchscreen, for 7 in touch-only panel mount	Consult
176126	Overlay, touchscreen, for 12 in touch-only panel mount	Consult
178161	Clear protective overlay display (pack of 5)	Consult
178163	Clear protective overlay keypad (pack of 5)	Consult

Options/Accessories

Part #	Description	Connector Type				Price
		Sealed		Unsealed		
USB Cables (Note: Cables have a plug)		A	B	A	B	
152434	Unsealed connectors USB-A to USB micro A, 2 m cable			X		Consult
79074	Unsealed connectors USB-A to USB-B, 2 m cable			X	X	Consult
124700	Sealed connectors, USB-A to USB-B, 3 m IP68 cable	X	X			Consult
126477	Sealed connector USB-A to unsealed connector USB-A, 3 m IP68 cable	X		X		Consult
124701	Sealed connector USB-A to unsealed connector USB-B, 3 m IP68 cable	X			X	Consult
124702	Sealed connector USB-B to unsealed connector USB-A, 3 m IP68 cable		X	X		Consult
USB Receptacles (Note: Receptacles have a socket)						
176790	Sealed receptacle USB-A for panel mount, 0,75 m cable	X		X		Consult
126476	Sealed receptacle USB-A for wall mount, 0,5 m cable	X		X		Consult
172735	Sealed receptacle USB-A for universal, 0,25 m cable	X		X		Consult
124694	Cover for sealed receptacles					Consult
124689	Cover for flash driver mounts on sealed receptacle					Consult
Ethernet Cables						
		Sealed		Unsealed		
72697	Unsealed Ethernet, RJ45 to RJ45, 2 m cable			X		Consult
124706	Sealed to sealed Ethernet 3 m cable	X				Consult
124707	Sealed to unsealed Ethernet 3 m cable	X		X		Consult
Ethernet Receptacles						
		Sealed		Unsealed		
176789	Sealed receptacle Ethernet RJ-45, 0,75 m cable	X				Consult
172734	Sealed receptacle Ethernet RJ-45, 0,5 m cable	X				Consult
126353	Sealed receptacle Ethernet RJ-45, 0,25 m cable	X				Consult