

Specifications

Cable Fittings:

P/N 88956:

- (4) PG7 0,118-0,255 strain relief
- (2) PG11 0,197-0,394 strain relief
- (1) PreVent™ breather vent

P/N 107700:

- (4) PG9 0,138-0,315 strain relief
- (2) PG11 0,197-0,394 strain relief
- (1) PreVent™ breather vent

Enclosure:

Stainless steel NEMA 4X/IP66

Connectors:

Spring clamp screwless, 12-28 AWG

Trimming:

Individual cell, signal trim

Potentiometers:

100 k ohm, 25 turn cermet

Circuit Board:

97 x 58 mm, with conformal coating

Warranty:

One-year limited warranty



Standard Features

- Stainless steel, NEMA 4X/IP66 enclosure
- Shunt jumpers to disable a load cell
- PreVent™ breather vent
- Conformal coated circuit board
- Number of cells: two to four single cells
- Expansion port

Approvals



Applications

- Floor, tank, hopper scales

Part Numbers

Part #	Description	Price
88956	JB4SS signal trim junction box with PG7 cord grips for load cells	Consult
107700	JB4SS signal trim junction box with PG9 cord grips for load cells	Consult
88958	Board only	Consult

Note: Do not mix junction box models or use other brands of junction boxes with Rice Lake junction boxes. There is a risk of system instability.

