

Specifications

- Cable Fittings:**
4 x M16, from load cells
1 x M16 from speed pickup
- Enclosure:**
Reinforced ABS, impact proof
- Connection:**
Terminal block, 2 mm²
- Operating Temperature:**
-40° C to 80° C (T6 as with II 2D)
- Protection:**
IP66
- Dimensions:**
260 x 160 x 90 mm
- Warranty:**
One-year limited warranty
- Approvals:**
ATEX



Standard Features

- Connection device for four load cells
- Connection for one speed pickup

Applications

- Summing four load cells
- Static weighing and belt scales

Part Numbers

Part #	Description	Est. Weight	Price
157584	J-Box, JBLA	2.050 g	Consult

Note: Do not mix junction box models or use other brands of junction boxes with Rice Lake junction boxes. There is a risk of system instability.

Specifications

- Cable Fittings:**
Two cord grips
- Enclosure:**
Stainless steel
- Connection:**
Terminal block
- Protection:**
IP66, T6 temperature
- Dimensions:**
200 x 120 x 64 mm
- Warranty:**
One-year limited warranty
- Approvals:**
ATEX



Standard Features

- Connection device for four load cells
- Connection for one speed pickup
- ATEX approved II2 G/D



Applications

- Summing four load cells
- Static weighing and belt scales

Part Numbers

Part #	Description	Price
157585	J-Box, JBLSA	Consult

Note: Do not mix junction box models or use other brands of junction boxes with Rice Lake junction boxes. There is a risk of system instability.