

Specifications

- Cable Fittings:**
Two cord grips
- Enclosure:**
Aluminum
- Connection:**
Terminal block
- Operating Temperature:**
-40° C to 80° C
- Dimensions:**
125 x 100 mm
- Warranty:**
One-year limited warranty
- Approvals:**
ATEX



Standard Features

- Connection device for one load cell
- Connection for one speed pickup
- ATEX approved

Approvals



Applications

- For splicing or extending load cell cables

Part Numbers

Part #	Description	Price
157583	J-Box, JBSA	Consult

Note: Do not mix junction box models or use other brands of junction boxes with Rice Lake junction boxes. There is a risk of system instability.

Specifications

- Cable Fittings:**
3 x M12, from load cell or speed pickup
2 x M16, to electronics
- Enclosure:**
Reinforced polycarbonate, impact proof
- Connection:**
Terminal block, 12 x 2 mm²
- Operating Temperature:**
-40° C to 80° C
- Protection:**
IP66
- Dimensions:**
180 x 110 x 90 mm
- Warranty:**
One-year limited warranty



Standard Features

- Connection device for two load cell
- Connection for one speed pickup

Applications

- Summing two load cells, belt scales and screw weigher

Part Numbers

Part #	Description	Est. Weight	Price
157579	J-Box, JBW, two cells	800 g	Consult

Note: Do not mix junction box models or use other brands of junction boxes with Rice Lake junction boxes. There is a risk of system instability.