

PROTOCOL CARDS
MODBUS-TCP® Interface
 880/1280™

Standard Features

- Active module with serial and parallel application interface
- Complete Modbus-TCP server
- Up to 8 bytes of I/O data in each direction
- Transformer isolated interface 100Mbps full duplex Ethernet
- Onboard diagnostic LEDs
- CE and UL compliant

Specifications

Dimensions:

52 x 48 x 19 mm

Power Requirements:

3,15-3,45 VDC

Operating Temperature:

-40° C to 85° C

Relative Humidity:

5-95% non-condensing

Connector Type:

RJ-45 (two with dual port version)



Part Number/Price

Part #	Description	Est. Weight	Price
179161	Modbus-TCP Interface kit for 880 (single port)	1 kg	Consult
165796	Modbus-TCP Interface kit for 1280 (single port)	1 kg	Consult

Options/Accessories

Part #	Description	Price
157939	Additional Modbus-TCP CD	Consult
156782	Additional operating manual	Consult

INDICATORS / CONTROLLERS

PROTOCOL CARDS
EtherNet/IP® Interface
 880/1280™

Standard Features

- Industrial protocol for AB PLC
- IP address settings configurable with web page, ARP or DHCP
- Supports Rockwell Automation EtherNet/IP
- Diagnostic LEDs
- CE marked and UL conformance

Specifications

Dimensions:

52 x 48 x 19 mm

Power Requirements:

3,15-3,45 VDC

Operating Temperature:

-40° C to 85° C

Relative Humidity:

5-95% non-condensing

Address Range:

Full IP address range



Part Number/Price

Part #	Description	Est. Weight	Price
179159	EtherNet/IP interface kit for 880 (single port)	1 kg	Consult
165792	EtherNet/IP interface kit for 1280 (single port)	1 kg	Consult

Options/Accessories

Part #	Description	Price
157943	Additional EtherNet/IP CD	Consult
156861	Additional operating manual	Consult

www.ricelake.com/global | Phone: +31 (0) 26 472 1319

RICE LAKE