

MSI-4260 IS Intrinsically Safe Crane Scale Port-A-Weigh



Standard Features

- Crane unit with five-digit, 30 mm LED display
- Top lifting eye or shackle, bottom thrust-bearing swivel hook
- 12 volt rechargeable battery and universal 115/230 VAC, 50/60 Hz battery charger (NA plug standard)

Additional Options

(Contact MSI for application consultation)

- NTEP Certified configuration

Approvals



Specifications

Accuracy:

± (0,1% +1 d) of applied load

Resolution:

3.000 to 5.000 d standard
(up to 10.000 d available)

Enclosure:

NEMA Type 4, IP66 marine grade 356 alloy anodized cast aluminum

Intrinsic Safety:

US Listings

FM16US0156X

IS / I, II, III / 1 / CDEFG / T4 Ta = -20°C to 50°C

I / 0 / AEx ia / IIB / T4 Ta = -20°C to 50°C Ga

20 / AEx ia / IIC / T135°C Ta = -20°C to 50°C Da

Canadian Listings

FM16CA0092X

IS / I / 1 / CD / T4 Ta = -10°C to 50°C

IS / II, III / 1 / EFG / T4 Ta = -10°C to 50°C

I / 0 / Ex ia / IIB / T4 Ta = -10°C to 50°C Ga

20 / Ex ia / IIC / T135°C Ta = -10°C to 50°C Da

ATEX Listings

FM16ATEX0038X

II 1 G Ex ia IIB T4 Ga -10°C ≤ Ta ≤ 50°C

II 1 D Ex ia IIC T135°C Da -10°C ≤ Ta ≤ 50°C

Lifting Eye, Shackle & Hook:

Crosby® or equal with 360° thrust-bearing swivel hook

Design Overload:

200% Safe / 500% Ultimate (except where noted)

Functions:

Power: Turns unit on or off

Zero: Zeros applied load up to 100% of capacity (limited range in NTEP Certified configuration)

Tare: Tares applied load and displays weight in Net mode F1: Programmable as test, units, net/gross, total and peak hold

Display:

Five-digit, 30 mm LED with programmable brightness control

Displayable Units:

Pounds or kilograms selectable

Annunciators:

COZ, Net, Gross, Total, Peak, Low Battery, lb/kg, Motion, Setpoints

Power:

12 volt rechargeable battery

115/230 VAC approved battery charger is included

Operating Time:

Up to 200 hours between charging with typical use

Auto-Off Mode:

Select for 15, 30, 45 minutes, 1 hour or select Off

Auto-Sleep Mode:

Power down during non-use and power up with weight change or any key press

Service Counters:

Counts number of lifts over percentage of capacity and lifts over capacity

Calibration:

Digital

Filtering:

OFF, LO, HI-1, HI-2 selectable

Warranty:

One-year limited warranty

Approvals:

NTEP CC 89-090 - 500 lb-2,000 lb
(250 kg-1,000 kg)

NTEP CC 89-090A1 - 5,000 lb-70,000 lb
(2,000 kg-35,000 kg)

MSI-4260 IS Intrinsically Safe Crane Scale Port-A-Weigh

Part Number/Price

Part #	Description	Capacity	Resolution	Price
156013	227 kg, Swivel Hook	500 lb (250 kg)	0.2 lb (0.1 kg)	Consult
156014	907 kg, Swivel Hook	2,000 lb (1,000 kg)	1.0 lb (0.5 kg)	Consult
156015	This should be 156018	5,000 lb (2,500 kg)	1.0 lb (0.5 kg)	Consult
156016		10,000 lb (5,000 kg)	2.0 lb (1.0 kg)	Consult
156017		20,000 lb (10,000 kg)	5.0 lb (2.0 kg)	Consult
156018		30,000 lb (15,000 kg)	10 lb (5.0 kg)	Consult
159019		50,000 lb (25,000 kg)	10 lb (5.0 kg)	Consult
156020		70,000 lb (35,000 kg)	20 lb (10 kg)	Consult
156021	45.359 kg, Swivel Hook	100,000 lb (50,000 kg)	20 lb (10 kg)	Consult
156022	22.680 kg, No attachments	50,000 lb (25,000 kg)	10 lb (5.0 kg)	Consult
156023	31.752 kg, No Attachments	70,000 lb (35,000 kg)	20 lb (10 kg)	Consult
156024	45.359 kg, No Attachments	100,000 lb (50,000 kg)	20 lb (10 kg)	Consult

Options/Assessories

Part #	Description	Price
170606	Battery Charger	Consult
167777	Spare Battery	Consult