

## Specifications

**Enclosure:**

NEMA 4, IP65

**Weight:**

445 g

**Keypad:**

On/off, zero (100%), tare, print, and two user-defined keys for the following functions: peak hold, high resolution, total, view total, net/gross, units switching

**Display:**

Six-digit 26,4 mm LCD

Units Displayed:

Pounds, kilograms, tons, metric tons, kilonewtons

**Annunciators:**

Stable, COZ, low battery, peak, net, kg, kN, lb, M, ton, setpoint, function LEDs

**Power:**

Integral lithium ion battery

Universal 115/230 VAC, 50/60 Hz battery charger (NA plug included)

**Operating Time:**

Up to 24 hours of continuous use (15 minute auto-shutoff with non-use)

**Operating Temperature:**

-20° C to 60° C

**RF Radio Link:**

2,4 GHz 802.15.4

Communicates with RF 3460, 4260, 7300, 7000 & 7001

**RF Effective Range:**

Typically 33 m

**Connector:**

4-Pin Turck connector for charging and RS-232 communication

**Warranty:**

One-year limited



## Standard Features

- Handheld RF remote display with six-digit 26,4 mm LCD screen
- Membrane keypad for remote control functionality
- User-definable function keys for added versatility
- Universal 115/230 VAC, 50/60 Hz battery charger (NA plug standard)
- Communicates with RF 4260, 7300, 7000 & 7001

## Part Number/Price

Part #	MSI Part #	Description	Price
139381	503208-0001	MSI-8000 RF remote display (requires ScaleCore™ equipped MSI-7300, MSI-4260, MSI-3460 and TranSend receivers)	Consult

## Options/Accessories

Part #	MSI Part #	Description	Price
149550	503486-0002	Universal 115/230 VAC 50/60 Hz (EC plug standard) battery charger for MSI 8000 RF remote display	Consult
150964	503489-0001	DB9 female serial interface cable for MSI-8000 RF remote display	Consult
151095	503506-0001	Audible alarm	Consult
182223		12V car charger adapter for MSI-8000	Consult

## Dimensions

	A	B	C	D
A	203 mm		C	98 mm
B	98 mm		D	35 mm

