

## PROTOCOL CARDS

## Profibus® DP Interface

880/1280™



## Part Number/Price

Part #	Description	Est. Weight	Price
179163	Profibus DP interface kit, for use with 880 indicator	1 kg	Consult
165795	Profibus DP interface kit for 1280 (single port)	1 kg	Consult

## Options/Accessories

Part #	Description	Price
157941	Additional GSD file	Consult
156784	Additional operating manual	Consult

## Standard Features

- DP intelligent slave
- Standard GSD file on disk
- 100 selectable addresses
- Up to 12Mbps baud rate

## Specifications

## Dimensions:

52 x 48 x 19mm

## Power Requirements:

3,15-3,45 VDC

## Operating Temperature:

-40° C to 85° C

## Warranty:

One-year limited warranty

## PROTOCOL CARDS

## Profinet® Interface

880/1280™



## Part Number/Price

Part #	Description	Est. Weight	Price
179160	Profinet interface kit for 880 (single port)	1 kg	Consult
165794	Profinet interface kit for 1280 (single port)	1 kg	Consult

## Options/Accessories

Part #	Description	Price
157940	Additional Profinet CD	Consult
156781	Additional operating manual	Consult

## Standard Features

- Profinet communication adapter
- Onboard diagnostic LEDs
- 100Mbps Baud Rate
- Works as an I/O device on the ProfiNet network
- PROFinergy compliant

## Specifications

## Dimensions:

52 x 48 x 19mm

## Power Requirements:

3,15-3,45 VDC

## Operating Temperature:

-40° C to 85° C

## IP Address Range:

Full IP address range DHCP

## Configuration:

GSDML file

## Connector Type:

RJ-45 (two with dual port version)