

RL-SEB

Bench Scales

BENCH SCALES



Specifications:

Load Cell, OIML Certified:
Stainless steel, IP67

Cable Length:
3 m

Compensated Temperature Range:
0° C to 40° C

Warranty:
One-year limited warranty

Standard Features

- 304 stainless steel construction
- Specially designed adjustable support feet provide exceptional traction and will not scratch surfaces

Approvals



Part Number/Price

Part #	Dimensions L x W x H (mm)	Max (kg)	e* (g)	Price
185879	230 x 330 x 90	3	1	Consult
185880	230 x 330 x 90	6	2	Consult
185881	230 x 330 x 90	15	5	Consult
185882	330 x 330 x 90	6	2	Consult
185883	330 x 330 x 90	15	5	Consult
185884	330 x 330 x 90	30	10	Consult
185885	400 x 400 x 115	15	5	Consult
185927	400 x 400 x 115	30	10	Consult
185928	400 x 400 x 115	60	20	Consult
185929	400 x 400 x 115	150	50	Consult
185930	400 x 500 x 115	30	10	Consult
185931	400 x 500 x 115	60	20	Consult
185932	400 x 500 x 115	150	50	Consult
185933	500 x 500 x 115	60	20	Consult
185934	500 x 500 x 115	150	50	Consult
185935	600 x 600 x 137	60	20	Consult
185936	600 x 600 x 137	150	50	Consult
185937	600 x 600 x 137	300	100	Consult

*Certified division size for Legal for Trade application

Options/Accessories

Part #	Description	Price
188201	Stainless steel column 350 mm with stainless steel fixings	Consult
188202	Stainless steel column 500 mm with stainless steel fixings	Consult
188203	Stainless steel column 700 mm with stainless steel fixings	Consult
188204	Stainless steel column 450 x 450 x 917 mm Ø 38 mm, stainless steel base	Consult
188205	Stainless steel column 450 x 450 x 917 mm Ø 38 mm, painted steel base	Consult
188206	Stainless steel column 350 x 350 x 750 mm, painted steel base	Consult
188240	Stainless steel fixing bracket for mounting RLT-200	Consult
188241	Stainless steel fixing bracket for mounting RLT-400	Consult
N/A	Installation, testing, configuration and verification	Consult factory

www.ricelake.com/global | Phone: +31 (0) 26 472 1319

RICELAKE

Dimensions

A	B	C	D	E	F
230 mm	330 mm	93 mm	178 mm	290 mm	30 mm
330 mm	330 mm	93 mm	278 mm	290 mm	30 mm
400 mm	400 mm	115 mm	345 mm	345 mm	30 mm
400 mm	500 mm	115 mm	345 mm	445 mm	30 mm
500 mm	500 mm	115 mm	445 mm	445 mm	30 mm
500 mm	600 mm	137 mm	435 mm	535 mm	30 mm
600 mm	600 mm	137 mm	535 mm	535 mm	30 mm

