

SINGLE-ENDED BEAM

RL1415

Stainless Steel, Hermetically Sealed, C3, IP68



Specifications

Full Scale Output:

2,0 mV/V

Output Resistance:

350 ohms ± 3

Input Resistance:

350 ohms ± 3

Material/Finish:

Stainless steel

Temperature:

-10° C to 40° C

Seal Type:

Hermetically sealed, IP68

Rated Excitation:

15V

Insulation Resistance:

5000 Megohms

Cable Length:

5 m

Cable Construction:

PVC

Cable Color Code:

Red+ Excitation
 Black.....- Excitation
 Green+ Signal
 White- Signal
 Yellow+ Sense
 Blue- Sense

Warranty:

One-year limited warranty

Approvals:

Complies with
 OIML R60 C3
 C4 available



Order Information

Picture is a representation of actual product

Load Rating	Part#	Price
10 kg*	169840	Consult
15 kg*	169841	Consult
25 kg	169842	Consult
50 kg	169843	Consult
100 kg	169844	Consult
150 kg	169845	Consult
200 kg	169846	Consult

* Capacities without CE Test Certificate

Dimensions

Nominal Capacity	A	B	C	D	E	F	G	H	I
mm									
10-200 kg	120	46,5	51,5	Ø42	22	Ø31	82,5	18	10

