


**Specifications**

- Full Scale Output:**  
2,0 mV/V
- Output Resistance:**  
350 ohms ± 3
- Input Resistance:**  
350 ohms ± 3
- Material/Finish:**  
Stainless steel
- Temperature:**  
-10° C to 40° C
- Seal Type:**  
Hermetically sealed, IP68
- Rated Excitation:**  
15V
- Insulation Resistance:**  
5.000 Megohms
- Cable Length:**  
5m
- Cable Construction:**  
PVC
- Cable Color Code:**  
 Red .....+ Excitation  
 Black.....- Excitation  
 Green .....+ Signal  
 White .....- Signal  
 Yellow .....+ Sense  
 Blue .....- Sense
- Warranty:**  
One-year limited warranty
- Approvals:**  
 Complies with  
 OIML R60 C3  
 C4 available
 



**Order Information**

*Picture is a representation of actual product*

Load Rating	Part#	Price
10 kg*	169825	Consult
15 kg*	169826	Consult
25 kg	169827	Consult
30 kg	169828	Consult
50 kg	169829	Consult
75 kg	169830	Consult
100 kg	169831	Consult
150 kg	169832	Consult
200 kg	169839	Consult
250 kg	169833	Consult
300 kg	169834	Consult
500 kg	169835	Consult
750 kg	169836	Consult
1000 kg	169837	Consult
1500 kg	169838	Consult

\* Capacities without CE Test Certificate

**Dimensions**

Nominal Capacity	A	B	C	D	E	F	G	H	I	J
mm										
10-1500 kg	136,5	52,5	53,5	30,5	∅50	22	∅30	82,5	25	16

