

## Specifications

**Full Scale Output:**  
2,0 mV/V

**Output Resistance:**  
350 ohms  $\pm$  3

**Input Resistance:**  
350 ohms  $\pm$  3

**Material/Finish:**  
Stainless steel

**Temperature:**  
-10° C to 40° C

**Seal Type:**  
Hermetically sealed, IP69K

**Rated Excitation:**  
15V

**Insulation Resistance:**  
5.000 Megohms

**Cable Length:**  
5 m

**Cable Construction:**  
PVC

**Cable Color Code:**

Red .....	+ Excitation
Black .....	- Excitation
Green .....	+ Signal
White .....	- Signal
Yellow .....	+ Sense
Blue .....	- Sense

**Warranty:**  
One-year limited warranty

**Approvals:**  
*Complies with  
OIML R60 C3  
C4 available*



## Order Information

*Picture is a representation of actual product*

Load Rating	Part#	Price
500 kg	<b>169812</b>	Consult
550 kg	<b>169813</b>	Consult
750 kg	<b>169815</b>	Consult
1000 kg	<b>169814</b>	Consult
1100 kg	<b>169816</b>	Consult
1500 kg	<b>169817</b>	Consult
1760 kg	<b>169818</b>	Consult

## Dimensions

Nominal Capacity	A	B	C	D	E	F	G	H	I	J	K
mm											
500/750/1000/1500 kg	13,5	57	2,5	13,5	M12	Ø13	16	25,4	76,2	31,5	130
550/1100/1760 kg	20,6	57	2,5	13,5	M12	Ø13	16	25,4	76,2	31,5	130

