

Specifications

- Full Scale Output:**
2,0 mV/V
- Output Resistance:**
350 ohms ± 3
- Input Resistance:**
350 ohms ± 3
- Material/Finish:**
Alloy steel
- Temperature:**
-10° C to 40° C
- Seal Type:**
Environmentally sealed, IP67
- Rated Excitation:**
15V
- Insulation Resistance:**
5.000 Megohms
- Cable Length:**
5 m
- Cable Construction:**
PVC
- Cable Color Code:**
 Red+ Excitation
 Black.....- Excitation
 Green+ Signal
 White- Signal
 Yellow+ Sense
 Blue- Sense
- Warranty:**
One-year limited warranty
- Approvals:**
Complies with
OIML R60 C3
C4 available



Order Information

Picture is a representation of actual product

Load Rating	Part#	Price
30 kg	173235	Consult
50 kg	173236	Consult
75 kg	173237	Consult
100 kg	173238	Consult
150 kg	173239	Consult
200 kg	173240	Consult
250 kg	173241	Consult
300 kg	173242	Consult

Dimensions

Nominal Capacity	A	B	C	D	E	F	G	H	I	J	K	L	M
mm													
30-300 kg	58	45,5	26,5	M12	31,5	15,5	13	130	31,5	16	25,4	76,2	12,4

