

SINGLE-ENDED BEAM

RL1444

Stainless Steel, Environmentally Sealed, C3, IP67



Specifications

Full Scale Output:
2,0 mV/V

Output Resistance:
350 ohms ± 3

Input Resistance:
350 ohms ± 3

Material/Finish:
Stainless steel

Temperature:
-10° C to 40° C

Seal Type:
Environmentally sealed, IP67

Rated Excitation:
15V

Insulation Resistance:
5.000 Megohms

Cable Length:
5 m

Cable Construction:
PVC

Cable Color Code:
Red+ Excitation
Black.....- Excitation
Green+ Signal
White- Signal
Yellow+ Sense
Blue- Sense

Warranty:
One-year limited warranty

Approvals:
Complies with
OIML R60 C3
C4/C5/C6 available

Order Information

Picture is a representation of actual product

Load Rating	Part #	Price
30 kg	169803	Consult
50 kg	169804	Consult
75 kg	169805	Consult
100 kg	169806	Consult
150 kg	169807	Consult
200 kg	169808	Consult
250 kg	169809	Consult
300 kg	169810	Consult

Dimensions

Nominal Capacity	A	B	C	D	E	F	G	H	I	J	K	L	M
mm													
30-300 kg	58	45,5	26,5	M12	31,5	15,5	13	130	31,5	16	25,4	76,2	12,4

