

## Specifications

**Full Scale Output:**  
2,0mV/V  $\pm$  0,1% mV/V

**Output Resistance:**  
350 ohms  $\pm$  3

**Input Resistance:**  
350 ohms  $\pm$  3

**Material/Finish:**  
Stainless steel

**Temperature:**  
-30°C to 70°C

**Seal Type:**  
Welded seal, IP67

**Rated Excitation:**  
5-15 VDC max.

**Insulation Resistance:**  
> 5.000 Megohms

**Cable Length:**  
5 m

**Cable Color Code:**

Red .....+ Excitation  
Black.....- Excitation  
Green .....+ Signal  
White .....- Signal  
Yellow .....+ Sense  
Blue .....- Sense

**Warranty:**  
One-year limited warranty

**Approvals:**



Complies with  
OIML R60 C3/C4



## Order Information

Picture is a representation of actual product

Load Rating	Part#	Price
2000 kg	173248	Consult
3000 kg	173249	Consult
4000 kg	173250	Consult
5000 kg	173251	Consult
7500 kg	173252	Consult

## Dimensions

Nominal Capacity	A	B	C	D	E	F	G	H
mm								
2000-4000 kg	175	35	98	32	45	40	19	74
5000-7500 kg	200	45	123	41	45	40	19	74

