

Specifications

- Full Scale Output:**
2,0mV/V
- Output Resistance:**
1.000 ohms ± 5
- Input Resistance:**
1.100 ohms ± 20
- Material/Finish:**
Stainless steel
- Temperature:**
-10° C to 50° C
- Seal Type:**
Welded seal, IP68
- Safe Overload:**
150% FS
- Rated Excitation:**
10VDC (15VDC Max)
- Combined Error:**
0.017% FS
- Insulation Resistance:**
> 5.000 Megohms
- Cable Length:**
5 m, 6 conductor
- Cable Color Code:**
Brown+ Excitation
Green- Excitation
Yellow+ Signal
White- Signal
Grey+ Sense
Pink- Sense

Warranty:
One-year limited warranty

Approvals:



Complies with
OIML R60 C3
C4 available



Order Information

Picture is a representation of actual product

Load Rating	Part Number	Price
500 kg	185178	Consult
1.000 kg	185179	Consult
2.000 kg	187627	Consult
2.500 kg	185181	Consult

Dimensions

Nominal Capacity	A	B	C	D	E	F	G	H	I	J	K	L	M	N
mm														
500-2.500 kg	132	76,3	25,4	18	Ø 3	6	18	31	9	31,5	M 12	Ø18	N°2 Ø13	N°2 Ø18

