

Specifications

- Full Scale Output:**
2,0mV/V
- Output Resistance:**
350 ohms, ± 3
- Input Resistance:**
400 ohms, ± 20
- Material Finish:**
Stainless steel
- Temperature:**
-10° C to 40° C
- Seal Type:**
Hermetically sealed, IP68/IP69K
- Safe Overload:**
200%
- Rated Excitation:**
10V
- Combined Error:**
<± 0,017%
- Insulation Resistance:**
>5.000 Megohms
- Cable Length:**
5 m
- Cable Construction:**
PVC
- Cable Color Code:**
Green+ Excitation
Black.....- Excitation
Red+ Signal
White- Signal
Blue+ Sense
Yellow- Sense

Warranty:
One-year limited warranty

Approvals:



Order Information

Picture is a representation of actual product

Load Rating	Part #	Est. Weight	Price
15 kg	160816	1,8 kg	Consult
20 kg	160817	1,8 kg	Consult
30 kg	160818	1,8 kg	Consult
50 kg	160819	1,8 kg	Consult
75 kg	160820	1,8 kg	Consult
120 kg	160821	1,8 kg	Consult
200 kg	160822	1,8 kg	Consult
350 kg	160823	1,8 kg	Consult
250 kg	161136	4,3 kg	Consult
400 kg	161137	4,3 kg	Consult
Options			
Consult	ATEX versions		Consult

Dimensions

Rated Capacity	A	B	C	D	E	F	G	H	I	J
mm										
15, 20, 30, 50, 75, 120, 200, 300 kg	8 x M8 x 1 x 14	35	50	56	35	17	96	20	150	35
250 - 400 kg	8 x M10 x 2 x 20	50	60	66	50	30	100	40	180	60

