

## Specifications

**Full Scale Output:**  
2,0mV/V  $\pm$  0.1% mV/V

**Output Resistance:**  
350 ohms  $\pm$  3

**Input Resistance:**  
350 ohms  $\pm$  3

**Material/Finish:**  
Alloy steel

**Temperature:**  
-30° C to 70° C

**Seal Type:**  
Welded seal, IP67

**Rated Excitation:**  
5–10 VDC max.

**Insulation Resistance:**  
> 5000 Megohms

**Cable Length:**  
5 m

**Cable Color Code:**

Red .....+ Excitation  
Black.....- Excitation  
Green .....+ Signal  
White .....- Signal  
Yellow .....+ Sense  
Blue .....- Sense

**Warranty:**  
One-year limited warranty

**Approvals:**

Complies with  
OIML R60 C3/C4



## Order Information

Picture is a representation of actual product

Load Rating	Part#	Price
750 kg	173299	Consult
1000 kg	173300	Consult
1500 kg	173301	Consult
2000 kg	173302	Consult
2500 kg	173303	Consult
3000 kg	173304	Consult
4000 kg	173305	Consult
5000 kg	173306	Consult
6000 kg	173307	Consult
10000 kg	173308	Consult

## Dimensions

Nominal Capacity	A	B	C	D
mm				
750 kg	80	80	35	M12
1.000 kg	80	80	35	M12
1.500 kg	80	80	35	M16
2.000 kg	80	80	42	M16
3.000 kg	80	80	42	M24x2
5.000 kg	80	80	42	M24x2
6.000 kg	80	80	42	M24x2
10.000 kg	80	80	52	M24x2

