

S-BEAM

# RL3434

Stainless Steel, Welded Seal, C4, IP67



## Specifications

- Full Scale Output:**  
2,0 mV/V  $\pm$  0.1% mV/V
- Output Resistance:**  
350 ohms  $\pm$  3
- Input Resistance:**  
350 ohms  $\pm$  3
- Material/Finish:**  
Stainless steel
- Temperature:**  
-30° C to 70° C
- Seal Type:**  
Welded seal, IP67
- Rated Excitation:**  
5–15 VDC max.
- Insulation Resistance:**  
> 5000 Megohms
- Cable Length:**  
5 m
- Cable Color Code:**

- Red .....+ Excitation
- Black.....- Excitation
- Green.....+ Signal
- White.....- Signal
- Yellow.....+ Sense
- Blue.....- Sense

**Warranty:**  
One-year limited warranty

**Approvals:**

Complies with  
OIML R60 C4



## Order Information

Picture is a representation of actual product

Load Rating	Part #	Price
750 kg	173309	Consult
1.000 kg	173310	Consult
1.500 kg	173311	Consult
2.000 kg	173312	Consult
2.500 kg	173313	Consult
4.000 kg	173314	Consult
5.000 kg	173315	Consult
6.000 kg	173316	Consult
10.000 kg	173317	Consult

## Dimensions

Nominal Capacity	C	D	E
mm			
750 kg	35	M12	80
1.000 kg	35	M12	80
1.500 kg	35	M16	80
2.000 kg	42	M16	80
2.500 kg	42	M16	80
4.000 kg	42	M24x2	80
5.000 kg	42	M24x2	80
6.000 kg	42	M24x2	80
10.000 kg	52	M24x2	80

