

SINGLE-POINT

# RL4454

Stainless Steel, Environmentally Sealed, C3/C4, IP67



## Specifications

**Full Scale Output:**

2,0 mV/V

**Output Resistance:**

350 ohms ± 3

**Input Resistance:**

390 ohms ± 3

**Material/Finish:**

Stainless steel

**Temperature:**

-30° C to 70° C

**Seal Type:**

Environmentally sealed, IP67

IP68 rating with fully welded seal is available

**Rated Excitation:**

5-15 VDC max.

**Insulation Resistance:**

> 5.000 Megohms

**Cable Length:**

5 m

**Cable Color Code:**

Red .....+ Excitation

Black.....- Excitation

Green .....+ Signal

White .....- Signal

Yellow .....+ Sense

Blue .....- Sense

**Warranty:**

One-year limited warranty

**Approvals:**

Complies with  
OIML R60 C3/C4



## Order Information

Picture is a representation of actual product

Load Rating	Part#	Price
150 kg	173408	Consult
300 kg	173409	Consult
500 kg	173410	Consult
750 kg	173411	Consult
1.000 kg	173412	Consult

## Dimensions

Nominal Capacity	A	B	C	D	E	F	G	H
mm								
150 - 1.000 kg	170	94	59	46	30	41	20	8

