

SINGLE-POINT

# RL4511

Aluminum, Environmentally Sealed, IP67



## Specifications

**Full Scale Output:**  
2,0 mV/V

**Output Resistance:**  
300-500 ohms

**Input Resistance:**  
300-500 ohms

**Material Finish:**  
Aluminum

**Temperature:**  
-10° C to 50° C

**Seal Type:**  
Environmentally sealed, IP67

**Safe Overload:**  
150% FS

**Rated Excitation:**  
10VDC (15VDC Max)

**Insulation Resistance:**  
>2.000 ohms

**Cable Length:**  
40 cm, 4 conductor

**Cable Construction:**  
PVC

**Cable Color Code:**  
Blue .....+ Excitation  
Black.....- Excitation  
White .....+ Signal  
Red .....- Signal

**Warranty:**  
One-year limited warranty

**Max Platform Size:**  
300 x 300 mm

**Approvals:**



## Order Information

Picture is a representation of actual product

Load Rating	Part#	Price
3 kg	185152	Consult
5 kg	185153	Consult
10 kg	185154	Consult
15 kg	185155	Consult
20 kg	185156	Consult
30 kg	185157	Consult
40 kg	185158	Consult

## Dimensions

Rated Capacity	A	B	C	D	E	F	G	H	I
mm									
3-40 kg	n° 4 M6	25,4	15	12	106	22	130	25	25

