

**Specifications**

- Full Scale Output:**  
2,0mV/V
- Output Resistance:**  
300-500 ohms
- Input Resistance:**  
300-500 ohms
- Material Finish:**  
Aluminum
- Temperature:**  
-10° C to 50° C
- Seal Type:**  
Environmentally sealed, IP67
- Safe Overload:**  
150% FS
- Rated Excitation:**  
10VDC (15VDC Max)
- Combined Error:**  
0,03% FS
- Insulation Resistance:**  
>2.000 ohms
- Cable Length:**  
3 m, 6 conductor
- Cable Color Code:**  
Blue .....+ Excitation  
Black .....- Excitation  
White .....+ Signal  
Red .....- Signal  
Green .....+ Sense  
Grey .....- Sense
- Warranty:**  
One-year limited warranty
- Max Platform Size:**  
450 x 450 mm

**Approvals:**



**Order Information**

*Picture is a representation of actual product*

Load Rating	Part#	Price
10 kg	185159	Consult
15 kg	185160	Consult
20 kg	185161	Consult
30 kg	185162	Consult
50 kg	185163	Consult
100 kg	185164	Consult
200 kg	185165	Consult

**Dimensions**

Rated Capacity	A	B	C	D	E	F	G	H	I	J	K
mm											
10-200 kg	N°7 M6	99,6	19,1	19,1	6,1	25,4	40	19,1	150	34	1

