

## Specifications

**Full Scale Output:**  
2,0mV/V

**Output Resistance:**  
359 ohms, ± 5

**Input Resistance:**  
380 ohms, ± 15

**Material Finish:**  
Stainless steel

**Temperature:**  
-10° C to 50° C

**Seal Type:**  
Potted, IP67

**Safe Overload:**  
300% FS

**Rated Excitation:**  
10VDC (15VDC Max)

**Insulation Resistance:**  
>1.000 Megohms

**Cable Length:**  
3 m, 6 conductor

**Cable Color Code:**  
 White .....+ Excitation  
 Red .....- Excitation  
 Blue .....+ Signal  
 Black.....- Signal  
 Green ..... + Sense  
 Grey .....- Sense

**Warranty:**  
One-year limited warranty

**Max Platform Size:**  
500 x 400 mm

**Approvals:**



## Order Information

*Picture is a representation of actual product*

Load Rating	Part #	Price
7,5 kg	185166	Consult
15 kg	185167	Consult
30 kg	185168	Consult
50 kg	185169	Consult
100 kg	185170	Consult
200 kg	185171	Consult

## Dimensions

Rated Capacity	A	B	C	D	E	F	G
mm							
7,5-200 kg	150	40	25	19	100	19	6,2

