

# RL5416

Stainless Steel, Welded Seal, OIML C4, IP69K



## Specifications

- Full Scale Output:**  
2,0 mV/V
- Output Resistance:**  
700 ohms, ± 3
- Input Resistance:**  
800 ohms, ± 3
- Material Finish:**  
Stainless steel
- Compensated Temperature:**  
-10° C to 40° C
- Operating Temperature:**  
-10° C to 70° C
- Seal Type:**  
Welded seal IP69 K
- Rated Excitation:**  
15V

- Vmin:**  
Emax/14000
- Insulation Resistance:**  
>5.000 megohms
- Cable Length:**  
20 m
- Cable Construction:**  
PVC
- Cable Color Code:**  
Red .....+ Excitation  
Black.....- Excitation  
Green .....+ Signal  
White .....- Signal  
Yellow .....+ Sense  
Blue .....- Sense

**Warranty:**  
Two-year limited warranty

**Approvals:**



R60 C4

## Order Information

Picture is a representation of actual product

Load Rating	Part #	Price
10t	168082	Consult
15t	168083	Consult
20t	168084	Consult
25t	168085	Consult
30t	168087	Consult
35t	168088	Consult
40t	168089	Consult
50t	168090	Consult

## Options

Part #	Description	Price
173793	Stainless steel cup set	Consult

## Dimensions

Rated Capacity	A	B	C	D	E	F	G	H
mm								
10 - 50t	88,4	30,8	Ø43,8	Ø88,9	41,5	Ø39,7	Ø46	Ø43,8

