

RL5416DC

Digital Stainless Steel, Hermetically Sealed, C4, IP68



Specifications

Transmission Speed:
100 kHz (max)

Current Consumption:
35 mA

Conversions Per Second:
40 s

Material Finish:
Stainless steel

Certified Temperature:
-10° C to 40° C

Operating Temperature:
-35° C to 70° C

Seal Type:
Hermetically sealed, IP68

Rated Excitation:
15V

Vmin:
Emax/15000

Insulation Resistance:
>5.000 megohms

Cable Length:
4 m, 7 m, 9m, 15 m, 25 m, 50 m

Cable Construction:
PVC

Warranty:
Two-year limited warranty

Approvals:



Order Information

Picture is a representation of actual product

Load Rating	Part #	Price
30t	195843	Consult
40t	195844	Consult

Cables					
1 Connector			2 Connector		
Length	Part #	Price	Length	Part #	Price
15 m	182733	Consult	4 m	182736	Consult
25 m	182734	Consult	7 m	182737	Consult
50 m	182735	Consult	9 m	182738	Consult

Options

Picture is a representation of actual product

Part #	Description	Price
173798	Stainless steel cup set	Consult

Dimensions

Rated Capacity	A	B	C	D	E	F	G	H
mm								
30 - 40t	150	88	Ø89	Ø44	25	36	32	Ø84

