

RL5426D

Digital, Stainless Steel, Hermetically Sealed, C6, IP69K



Specifications

- Transmission Speed:**
100 kHz (max)
- Current Consumption:**
35 mA
- Conversion per Second:**
40 s
- Material/Finish:**
Stainless steel
- Certified Temperature:**
-10° C to 40° C
- Operating Temperature:**
-20° C to 70° C
- Seal Type:**
Hermetically sealed, IP69K
- Rated Excitation:**
15V
- Vmin:**
Emax/18000
- Insulation Resistance:**
>5000 Megohms
- Cable Length:**
15 m
- Cable Construction:**
PVC
- Warranty:**
Two-year limited warranty
- Approvals:**
EU
LEGAL FOR TRADE CERTIFIED

Order Information

Picture is a representation of actual product

Load Rating	Part#	Price
10 t	177779	Consult
15 t	177780	Consult
20 t	177781	Consult
25 t	177782	Consult
30 t	177783	Consult
35 t	177784	Consult
40 t	177785	Consult
50 t	177786	Consult

*Versions with connectors available, consult factory

Options

Part#	Description	Price
173798	Stainless steel cup set	Consult

Dimensions

Rated Capacity	A	B	C	D	E	F	G	H
mm								
10 - 50t	73,7	23,4	21,4	Ø56,8	Ø88,9	Ø50,5	52,5	Ø43,8

