

Specifications

- Transmission Speed:**
100 kHz (max)
- Current Consumption:**
35 mA
- Conversion per Second:**
40 s
- Material/Finish:**
Stainless steel
- Certified Temperature:**
-10° C to 40° C
- Operating Temperature:**
-35° C to 70° C
- Seal Type:**
Hermetically sealed, IP68
- Rated Excitation:**
15VDC / 8 ÷ 15
- Vmin:**
Emax/18000
- Insulation Resistance:**
5000 Megohms
- Cable Length:**
4 m, 7 m, 9m, 15 m, 25 m, 50 m
- Cable Construction:**
Polyurethane
- Warranty:**
Two-year limited warranty
- Approvals:**



Order Information

Picture is a representation of actual product

Load Rating	Part #	Price
30t	195845	Consult
40t	195846	Consult

Cables					
Length	1 Connector		2 Connector		Price
	Part #	Price	Part #	Price	
15 m	182733	Consult	4 m	182736	Consult
25 m	182734	Consult	7 m	182737	Consult
50 m	182735	Consult	9 m	182738	Consult

Options

Picture is a representation of actual product

Part #	Description	Price
173798	Stainless steel cup set	Consult

Dimensions

Rated Capacity	A	B	C	D	E	F	G	H	I
mm									
30 - 40t	ø089	114	ø51	ø44	74	36	36	ø9	ø84

