

RL6515

Stainless Steel, Welded Seal, IP68



Specifications

Full Scale Output:
2,0 mV/V

Output Resistance:
700 ohms ± 5

Input Resistance:
750 ohms ± 10

Material/Finish:
Stainless steel

Temperature:
-10° C to 40° C

Seal Type:
Welded seal, IP68

Safe Overload:
120% FS

Rated Excitation:
10 VDC (15VDC max)

Combined Error:
0.05% FS

Insulation Resistance:
> 5.000 Megohms

Cable Length:
5 m 250-5.000 kg
10 m 7.500-100.000 kg

Cable Color Code:
Red+ Excitation
Black.....- Excitation
Green.....+ Signal
White.....- Signal

Warranty:
One-year limited warranty

Approvals:
Complies with
OIML R60
Capacities
2.500 to 12.500



Order Information

Picture is a representation of actual product

Load Rating	Part Number	Price
250 kg	185195	Consult
500 kg	185196	Consult
1.000 kg	185197	Consult
2.500 kg	185198	Consult
5.000 kg	185199	Consult
7.500 kg	185200	Consult
12.500 kg	185201	Consult
15.000 kg	185202	Consult
30.000 kg	185203	Consult
50.000 kg	185204	Consult
100.000 kg	185205	Consult
Mounts		
250-12.500 kg	185208	Consult
15.000 kg	185209	Consult
30.000 kg	185210	Consult
50.000-100.000 kg	185211	Consult
250-12.500 kg alloy steel	185212	Consult

Dimensions

Nominal Capacity	A	B	C	D	E	F
mm						
250-12.500 kg	Ø82	Ø22	44	32	N°3 M8	Ø70
15.000 kg	Ø100	Ø28	48,5	35	N°3 M10	Ø80
30.000 kg	Ø126	Ø35	54	40	N°3 M12	Ø90
50.000-100.000 kg	Ø165	Ø60	80	60	N°3 M16	Ø130

