

# RL97

Stainless Steel, Welded Seal, C3/C4, IP69K



## Specifications

**Full Scale Output:**  
2,0 mV/V

**Output Resistance:**  
700 ohms, ±3

**Input Resistance:**  
800 ohms, ±3

**Material Finish:**  
Stainless steel

**Temperature:**  
-10° C to 40° C

**Seal Type:**  
Welded seal, IP69K

**Safe Overload:**  
150%

**Rated Excitation:**  
15V

**Combined Error:**  
0,02%

**Insulation Resistance:**  
>5.000 megohms

**Cable Length:**  
15 m

**Cable Construction:**  
PVC

**Cable Color Code:**  
 Red .....+ Excitation  
 Black.....- Excitation  
 Green .....+ Signal  
 White .....- Signal  
 Yellow .....+ Sense  
 Blue .....- Sense

**Warranty:**  
One-year limited warranty

**Approvals:**  
Complies with  
OIML R60 C3/C4

## Order Information

Picture is a representation of actual product

Load Rating	Part#	Price
15t	161293	Consult
20t	161294	Consult
25t	161295	Consult
30t	161296	Consult
35t	161297	Consult
40t	161298	Consult
50t	161299	Consult
75t	161300	Consult
100t	161301	Consult
200t	161302	Consult

## Dimensions

Rated Capacity	A	B	C	D
mm				
15 - 40t	44	89	18	99
50 - 100t	56	114	19	127

