

Specifications

Enclosure:

ABS IP54 case

Keyboard:

Five-key functional waterproof, On/Off, Zero, Tare, Mode and Print

Display:

Six-digit 25 mm LCD backlight

Units Displayed:

Kilograms, pounds, tons, grams

Power:

12 VDC with included external power adapter (240 VAC, 50/60 Hz)
4-AA batteries

Operating Temperature:

Legal for Trade: -10° C to 40° C
Industrial: -10° C to 60° C

A/D Inputs:

24 bit, four-channel converter, max. 200 conv./sec. autoselect, and up to eight signal linearisation points

Resolution:

Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points

Load Cell Excitation:

5 VDC

Data I/O:

(2) RS-232/C (1) printer (1) PC

Optional Communications:

RS-485, Bluetooth

Printer Compatibility:

LP542S

Warranty:

Two-year

Approvals:

EC Type Approval (EN45501)



Standard Features

- Five-key waterproof keypad
- High contrast six-digit and icon, 25 mm LCD backlit screen
- Selectable function modes: high resolution x 10, net/gross, lb to kg conversion, total, formulation, +/- controller with quick target and threshold input, percentage weighing, piece counter, hold
- Easy-to-clean ABS IP54 case, resistant to harsh and corrosive environments

APPROVALS



Part Number/Price

Part #	Description	Price
185279	RLT-200, 5-12VDC, 4AA batteries	Consult

Options/Accessories

Part #	Description	Price
185299	RS-485	Consult
185300	Alibi memory (includes clock)	Consult
181885	Bluetooth	Consult
193500	EPROM	Consult