

Specifications

Enclosure:

IP68 stainless steel case with sealed rubber gasket

Keypad:

17-key functional waterproof, Zero, Automatic Tare, Presettable Tare, Print, On/Off, Database of 30 Tares, Two Numeric IDs, Keyboard Lock, and Repetition of last printout

Display:

Six-digit 25 mm LCD backlight

Units Displayed:

Kilograms, pounds, tons, grams

Power:

110-240 VAC internal power adapter

Operating Temperature:

Legal for Trade: -10° C to 40° C
Industrial: -10° C to 60° C

A/D Inputs:

24 bit, four-channel converter, max. 200 conv./sec. autoselect, and up to eight signal linearisation points

Resolution:

Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points

Load Cell Excitation:

5 VDC

Data I/O:

(2) RS-232/C bidirectional port (1) IPC (1) printer

Optional Communications:

RS-485, Bluetooth

Warranty:

Two-year

Approvals:

EC Type Approval (EN45501)



Standard Features

- 17-key waterproof keypad
- High contrast six-digit and icon, 25 mm LCD backlit screen
- Selectable function modes high resolution x 10, net/gross or lb to kg conversion, total, formulation, +/- checkweighing, percentage weighing, counting
- IP68 stainless steel case with sealed rubber gasket

APPROVALS



Part Number/Price

Part #	Description	Price
185262	RLT-400, 110-240 VAC	Consult

Options/Accessories

Part #	Description	Price
185348	Digital I/O	Consult
185298	Ethernet	Consult
185299	RS-485	Consult
185300	Alibi memory (includes clock)	Consult
181885	Bluetooth®	Consult
185360	UK power cord	Consult
185361	Swiss power cord	Consult
193500	EPROM	Consult