



Standard Features

- Large, 16,5 mm-high, backlit liquid crystal display (LCD)
- Selectable modes: Weight, Unit Count and Percentage
- 12 units of measurement
- Mono-Metal Tuning Fork Sensor (MMTF) provides quick response and stability
- 20-step bar graph display
- 115VAC adapter included (230VAC optional)
- Semi-automatic calibration, external weight
- Plastic housing on models < 1.000 g, plastic top and die cast bottom on models > 1.000 g

Optional Features

- RS-232
- Rechargeable battery

Specifications

	TC-620	TC-1200	TC-4200	TC-6200	
Part#	107232	107233	107234	107235	
Price	Consult	Consult	Consult	Consult	
Capacity	620 g	1.200 g	4.200 g	6.200 g	
Resolution	0,01 g	0,1 g	0,1 g	0,1 g	
Operating Modes	Count, Percentage, Limit Function (checkweighing)				
Repeatability	1 division				
Linearity	1 division				
Operating Temperature	5° C to 35° C				
Pan Size	139.7 mm	170.2 x 142.2 mm	177.8 x 157.5 mm		
Dimensions	234 x 180 x 74 mm		264 x 191 x 86 mm		
Weight (Approx.)	1,3 kg		2,7 kg		
Calibration Weight	600 g	1.200 g	4.000 g	6.200 g	
Power	120 VAC adapter				
Warranty	Five-year Limited Warranty				
Return Policy	Rice Lake Standard Policy				
UNIT OF MEASURE	Decimal Ounce	21 x 0,0005 oz	42 x 0,005 oz	140 x 0,005 oz	210 x 0,005 oz
	Decimal Pound	1,3 x 0,00005 lb	2,6 x 0,0005 lb	9,2 x 0,0005 lb	13 x 0,0005 lb
	Troy Ounce	19 x 0,0005 ozt	38 x 0,005 ozt	130 x 0,005 ozt	190 x 0,005 ozt
	Pennyweight	390 x 0,01 dwt	770 x 0,1 dwt	2.700 x 0,1 dwt	3.900 x 0,1 dwt
	Carat	3.100 x 0,05 ct	6.000 x 0,5 ct	21.000 x 0,5 ct	31.000 x 0,5 ct
	Momme	160 x 0,005 mom	320 x 0,05 mom	1.100 x 0,05 mom	1.600 x 0,05 mom
	Grain Unit	9.500 x 0,2 GN	18.000 x 2 GN	64.000 x 2 GN	95.000 x 2 GN
	Tael (Hong Kong)	16 x 0,0005 TL	32 x 0,005 TL	110 x 0,005 TL	160 x 0,005 TL
	Tael (Singapore, Malaysia, Taiwan)	16 x 0,0005 TL	31 x 0,005 TL	110 x 0,005 TL	160 x 0,005 TL
	Tola	53 x 0,001 to	100 x 0,01 to	360 x 0,01 to	530 x 0,01 to

Part Number/Price

Part #	Model #	Description	Price
107232	TC-620	620 g x 0,01 g	Consult
107233	TC-1200	1.200 g x 0,1 g	Consult
107234	TC-4200	4.200 g x 0,1 g	Consult
107235	TC-6200	6.200 g x 0,1 g	Consult

Options/Accessories

Part #	Description	Price
107236	Rechargeable battery-TC-620, TC-1200, 32 hr	Consult
107237	Rechargeable battery-TC-4200, TC-6200, 32 hr	Consult
107238	RS-232 option with DIN-5-Pin connector (not compatible with battery option) (TC-620, TC-1200)	Consult
107239	RS-232 option with DIN-5-Pin connection (not compatible with battery option, (TC-4200,TC-6200)	Consult
107240	In-use dust cover, 620 g to 1200 g	Consult
107250	In-use dust cover, 4.200 g to 6.200 g	Consult
109236	Underweigh hook TC-620, TC-1200	Consult
109292	Underweigh hook TC-4200, TC-6200	Consult
42566	120VAC adapter	Consult
42168	230VAC adapter	Consult
107243	Additional operating manual	Consult
75351	WinWedge software	Consult
115303	Five-pin to nine-pin RS-232 cable	Consult
115148	RS-232 manual	Consult